

C&C GRAFFITI REMOVER FOR POROUS SURFACES [12810]

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Date of issue: 04/04/2017 Revision date: 05/06/2015 Version: 10.0

C&C GRAFFITI REMOVER FOR POROUS SURFACES [12810]

12810

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

: Mixture Product form

: C&C GRAFFITI REMOVER FOR POROUS SURFACES [12810] Product name

Product code 12810 Type of product : Aeroso Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

Industrial/Professional use spec : For professional use only

Use of the substance/mixture : Graffiti remover

1.2.2 Uses advised against

No additional information available

Details of the supplier of the safety data sheet

NATIONWIDE HYGIENE SUPPLIES LTD, PEAK BUSINESS PARK, FOXWOOD ROAD, CHESTERFIELD, DERBYSHIRE, S41 9RF, UNITED KINGDOM
Tel: 0844 499 6380 Fax: 0844 499 6382 Email: sales@nationwide-hygiene.com **NATIONWIDE HYGIENE SUPPLIES**

Emergency telephone number

Emergency number : Mon to Fri 8.30am to 5.00pm - 0844 499 6380

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

H222:H229 Aerosol 1 Eye Dam. 1 H318

Full text of H-phrases: see section 16

Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02 GHS05

Signal word (CLP) : Danger

Hazardous ingredients : Oxirane, 2-methyl-, polymer with oxirane, mono(2-propylheptyl) ether, Oxirane, 2-methyl-,

polymer with oxirane, mono(2-propylheptyl) ether

Hazard statements (CLP) H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated

H318 - Causes serious eye damage : P102 - Keep out of reach of children

Precautionary statements (CLP) P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use

P280 - Wear eye protection

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P315 - Get immediate medical advice/attention

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Other hazards

No additional information available

Page 1 of 8 Document generated @ 04/04/2017 18:50:06

according to Regulation (EC) No. 453/2010

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dimethyl sulphoxide substance with national workplace exposure limit(s) (DE)	(CAS No) 67-68-5 (EC no) 200-664-3 (REACH-no) 01- 2119431362-50	30 - 60	Not classified	Not classified
propylene carbonate	(CAS No) 108-32-7 (EC no) 203-572-1 (EC index no) 607-194-00-1	5 - 15	Xi; R36	Eye Irrit. 2, H319
butane substance with national workplace exposure limit(s) (DK, GB, IE)	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0	5 - 15	F+; R12	Flam. Gas 1, H220 Press. Gas
Oxirane, 2-methyl-, polymer with oxirane, mono(2-propylheptyl) ether	(CAS No) Polymer_DT01	1 - 5	Xn; R22 Xi; R41	Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318
Oxirane, 2-methyl-, polymer with oxirane, mono(2-propylheptyl) ether	(CAS No) Polymer_DT03	1 - 5	Xn; R22 Xi; R41	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
propane substance with national workplace exposure limit(s) (DK, IE)	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5	1 - 5	F+; R12	Flam. Gas 1, H220

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Get medical advice/attention if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash with plenty of soap and water.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/injuries after eye contact : Causes eye irritation.

Symptoms/injuries after ingestion : May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. Explosion hazard : Explosion risk in case of fire.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required.

Document generated @ 04/04/2017 18:50:06 Page 2 of 8

according to Regulation (EC) No. 453/2010

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Do not spray on an open flame or other ignition source.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Does not require any specific or particular technical measures.

Storage conditions : Keep away from ignition sources. Protect from sunlight. Do not expose to temperatures

exceeding 50 °C/122 °F.

Incompatible products : Oxidizing agent. Strong acids. Strong bases.

Incompatible materials : Direct sunlight. Heat sources. Sources of ignition.

Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Dimethyl sulphoxide (67-68-	5)	
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	160 mg/m³
Germany	TRGS 900 Limitation of exposure peaks (mg/m³)	320 mg/m³
propane (74-98-6)		
Denmark	Local name	Propan
Denmark	Grænseværdie (langvarig) (mg/m³)	1800 mg/m³
Denmark	Grænseværdie (langvarig) (ppm)	1000 ppm
Ireland	Local name	Propane
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
Ireland	Notes (IE)	Asphx
butane (106-97-8)		
Denmark	Local name	n-Butan
Denmark	Grænseværdie (langvarig) (mg/m³)	1200 mg/m³
Denmark	Grænseværdie (langvarig) (ppm)	500 ppm
Ireland	Local name	Butane
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
United Kingdom	Local name	Butane
United Kingdom	WEL TWA (mg/m³)	1450 mg/m³
United Kingdom	WEL TWA (ppm)	600 ppm
United Kingdom	WEL STEL (mg/m³)	1810 mg/m³
United Kingdom	WEL STEL (ppm)	750 ppm
United Kingdom	Remark (WEL)	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)

Document generated @ 04/04/2017 18:50:06 Page 3 of 8

according to Regulation (EC) No. 453/2010

8.2. Exposure controls

Materials for protective clothing : Not required for normal conditions of use

Hand protection : In case of repeated or prolonged contact wear gloves

Eye protection : Safety glasses

Skin and body protection : Not required for normal conditions of use

Respiratory protection : Not required for normal conditions of use



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

: Liquid Physical state Appearance : Aerosol. : Colourless. Colour Odour characteristic. : No data available Odour threshold : No data available рΗ : No data available Relative evaporation rate (butylacetate=1) Melting point : No data available Freezing point : No data available : No data available Boiling point : No data available Flash point Auto-ignition temperature : No data available : No data available Decomposition temperature Flammability (solid, gas) : No data available Vapour pressure : No data available Relative vapour density at 20 °C No data available

Relative density : 0.9

Solubility : No data available
Log Pow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Direct sunlight. Heat. Open flame.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

Document generated @ 04/04/2017 18:50:06 Page 4 of 8

according to Regulation (EC) No. 453/2010

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

HFAVY	DUITY	GRAFFITI	REMOVER

Vaporizer Aerosol

SECTION 12: Ecological information

12.1. Toxicity

Oxirane, 2-methyl-, polymer with oxirane, mono(2-propylheptyl) ether (Polymer_DT01)		
LC50 fishes 1	> 10 - 100 mg/l	
EC50 Daphnia 1	> 10 - 100 mg/l	
FrC50 (other aquatic plants)	> 10 - 100 mg/l	

Oxirane, 2-methyl-, polymer with oxirane, mono(2-propylheptyl) ether (Polymer_DT03)		
LC50 fishes 1	> 10 - 100 mg/l	
EC50 Daphnia 1	> 10 - 100 mg/l	
ErC50 (other aquatic plants)	> 10 - 100 mg/l	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Dimethyl sulphoxide (67-68-5)	
Log Pow	-1.35

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Do not pierce or burn, even after use.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1950 UN-No. (IMDG) : 1950 UN-No.(IATA) : 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS

Proper Shipping Name (IATA) : AEROSOLS, FLAMMABLE

Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D)

Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1

Document generated @ 04/04/2017 18:50:06 Page 5 of 8

according to Regulation (EC) No. 453/2010

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 2.1 Danger labels (ADR) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1 Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1 Hazard labels (IATA) : 2.1



Packing group

Packing group (ADR) : Not applicable Packing group (IMDG) : Not applicable : Not applicable Packing group (IATA)

Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1L Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP02 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9 Transport category (ADR) : 2 Special provisions for carriage - Packages : V14 (ADR)

Special provisions for carriage - Loading,

: CV9, CV12 unloading and handling (ADR)

Special provisions for carriage - Operation : S2

(ADR)

Tunnel restriction code (ADR) : D

Document generated @ 04/04/2017 18:50:06

Page 6 of 8

according to Regulation (EC) No. 453/2010

- Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP02

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D

EmS-No. (Fire): F-DEmS-No. (Spillage): S-UStowage category (IMDG): None

- Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 1, slightly hazardous to water (Classification according to VwVwS,

Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Press. Gas	Gases under pressure
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H229	Pressurised container: May burst if heated
H302	Harmful if swallowed
H312	Harmful in contact with skin

Document generated @ 04/04/2017 18:50:06 Page 7 of 8

C&C GRAFFITI REMOVER FOR POROUS SURFACES [12810]

12810

Safety Data Sheet

according to Regulation (EC) No. 453/2010

H318	Causes serious eye damage
H319	Causes serious eye irritation

SDS EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

Document generated @ 04/04/2017 18:50:06 Page 8 of 8